



## NASA STTR 2017 Phase I Solicitation

### T8.02 Photonic Integrated Circuits

Lead Center: GSFC

Technology Area: TA8 Science Instruments, Observatories & Sensor Systems

Integrated photonics generally is the integration of multiple lithographically defined photonic and electronic components and devices (e.g., lasers, detectors, waveguides/passive structures, modulators, electronic control and optical interconnects) on a single platform with nanometer-scale feature sizes. The development of photonic integrated circuits permits size, weight, power and cost reductions for spacecraft microprocessors, communication buses, processor buses, advanced data processing, and integrated optic science instrument optical systems, subsystems and components. This is particularly critical for small spacecraft platforms. On July 27, 2015 - Vice President Joe Biden, at an event in Rochester, NY, announced the New York consortium has been selected to lead the Integrated Photonics Institute for Manufacturing Innovation. For details see (<http://manufacturing.gov/ip-imi.html>). Proposed as part of President Obamas National Network for Manufacturing Innovation (NNMI), the IP-IMI was established to bring government, industry and academia together to advance state-of-the-art photonics technology and better position the United States relative to global competition in this critical field. The use of the IP-IMI for work proposed under this topic is highly encouraged. This topic solicits methods, technology and systems for development and incorporation of active and passive circuit elements for integrated photonic circuits for:

- Integrated photonic sensors (physical, chemical and/or biological) circuits: NASA applications examples include (but are not limited to): Lab-on-a-chip systems for landers, Astronaut health monitoring, Front-end and back-end for remote sensing instruments including trace gas lidars Large telescope spectrometers for exoplanets using photonic lanterns and narrow band filters. On chip generation and detection of light of appropriate wavelength may not be practical, requiring compact hybrid packaging for providing broadband optical input-output and also, as means to provide coupling of light between the sensor-chip waveguides and samples, unique optical components (e.g., Plasmonic waveguides, microfluidic channel) may be beneficial.
- Integrated Photonic Circuits for Analog RF applications: NASA applications include new methods due to Size, Weight and Power improvements, passive and active microwave signal processing, radio astronomy and TeraHertz spectroscopy. As an example, integrated photonic circuits having very low insertion loss (e.g., ~1dB) and high spur free dynamic range for analog and RF signal processing and transmission which incorporate, for example, monolithic high-Q waveguide microresonators or Fabry-Perot filters with multi-GHz RF pass bands. These components should be suitable for designing chip-scale tunable opto-electronic RF oscillator and high precision optical clock modules.
- Integrated photonic circuits for very high speed computing: Advanced computing engines that approach TeraFLOP per second computing power for spacecraft in a fully integrated combined photonic and electronic package.

